

ARIZONA COURTLINES, INC. (ACI)
FBGP-5S - FOOTBALL GOAL POST (5-9/16" DIA. STRAIGHT POST)

- A. Support post, 5-9/16" outside diameter steel (A53) pipe.
- B. Crossbar, 5" outside diameter steel (A53) pipe.
- C. Crossbar's upper edge 10'-0" above playing field surface.
- D. Uprights, 2-1/2" outside diameter steel (A53) pipe.
- E. Uprights spacing: 23'-4" inside to inside.
- F. Uprights extend 30'-0" above playing field surface.
- G. Heavy-duty adjustable sleeves located on crossbar ends for upright leveling.
- H. Welded steel caps on crossbar and upright ends.
- I. 1/2" diameter grade 8 zinc plated hardware for crossbar and upright positioning.
- J. 3/8" diameter grade 5 zinc plated self-threading bolts at all connections.
- K. Installer to drill for 3/8" self-threading bolts.
- L. All hardware zinc plated.
- M. All pipe galvanized finish.
- N. Paint by others after installation if required.
- O. Powder coat finish available (additional cost).
- P. Footing: 3'-0" diameter x 4'-0" deep. Post 3'-6" into footing.
- Q. Steel anchor pin welded to bottom of support post to prevent removal and twisting.
- R. One year parts warranty.