

SPECIFICATIONS:

SOLID BRASS CASTING

TOP SURFACE GROUND FLAT AND CLEAR SEALED FELT PAD CUSHION BETWEEN COVER PLATE AND BASE FOUR MOUNTING HOLES (ANCHORS NOT INCLUDED) 1/8" DIAMETER SOLID STEEL PIVOT PIN EASY OPEN KEY HOLE (KEYS, PENS, PENCILS, ETC.) FOR USE WITH 4" O.D. POSTS AND SMALLER FOR USE ON ALL TYPES OF FLOORS SOLD AS ASSEMBLY ONLY

ONE YEAR WARRANTY (PARTS AND FACTORY LABOR)

INSTALL NOTES:

DIMENSIONS VARY SLIGHTLY.

DO NOT CUT HOLES UNTIL YOU HAVE COVER PLATE ASSEMBLY. MEASURE ACTUAL COVER PLATE, CUT AND DRILL ACCORDINGLY. TOP OF BASE RING AND COVER PLATE TO BE EVEN WITH PLAYING SURFACE. CONCRETE CHIPPING MAY BE REQUIRED FOR CERTAIN FLOORS.

FOR WOOD FLOORS USE WOOD SCREWS.

FOR CONCRETE OR TILE USE SCREW WITH EXPANSION SHIELDS.

CENTER COVER ASSEMBLY WITH SLEEVE .

| REVISION / STAGE: MONTH / DAY / YEAR | RELATED DRAWINGS / INFORMATION: |
|--------------------------------------|---|
| | |
| | |
| | |
| | |
| FS-CPB3 | THIS DRAWING IS PROPERTY OF ARIZONA COURTLINES, INC. AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION |

FS-CPB3

FLOOR SLEEVE COVER PLATE BRASS HINGED (4" MAX. POST) ARIZONA COURTLINES, INC.



8742 NORTH 78 TH AVENUE PEORIA, ARIZONA 85345 PHONE (623) 939 - 8126 FAX (623) 939 - 2526 WWW.ARIZONACOURTLINES.COM

DRAWN BY:

EDDIE CAFFERATA

CHECKED BY:

QUANTITY: