



HOOK & LOOP FASTENER LOCATIONS DETERMINED BY INSTALLER TO BEST FIT PROJECT CONDITIONS

- SPECIFICATIONS:**
- 14 OZ. VINYL COATED POLYESTER FABRIC
 - VINYL WRAPPED 2" AROUND BACKSIDE OF WOOD
 - VINYL FINISH STAPLED TO WOOD EVERY 3"
 - VINYL TREATMENTS: ANTI-MILDEW & U.V.
 - VINYL FINISH: LEATHER
 - VINYL DENIER: 1300
 - PASSES CSFM & NFPA-701 FIRE TESTS
 - 2" THICK OPEN CELL FOAM
 - FOAM DENSITY: 1.5 TO 6 LBS.
 - FOAM COMPRESSION SET: 90%
 - FOAM TEAR RESISTANCE: 1.2 LBS. PER LINEAR INCH
 - FOAM TENSILE STRENGTH: 12-18 PSI
 - WOOD BACKING: 3/8"-7/16" ORIENTED STRAND BOARD
 - 1-YEAR WARRANTY

MODEL # WP-26-RB
 WALL PAD
 2'-0" WIDE
 6'-0" HIGH
 REMOVABLE

REVISION / STAGE:	MONTH / DAY / YEAR	RELATED DRAWINGS / INFORMATION:

WALL PAD (REMOVABLE)

**VINYL COVERED REMOVABLE WALL PAD
(HOOK & LOOP FASTENERS)**

ARIZONA COURTLINES, INC.
 8742 NORTH 78TH AVENUE, PEORIA, ARIZONA 85345
 TEL. 623.939.8126 FAX. 623.939.2526
 www.ARIZONACOURTLINES.com

DRAWN BY: EDDIE CAFFERATA QUANTITY: _____

WP- __ - RB

THIS DRAWING IS PROPERTY OF ARIZONA COURTLINES, INC. AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION